

MEPNN Supplier Scouting Opportunity Synopsis

Section 1: General Information

Scouting Number	2024-273
Item to be Scouted	Heat Exchanger for HVAC
Days to be scouted	30
Response Due By	10/11/2024
Description	<p>For the construction of the new Energy and Minerals Research Facility (EMRF) for the U. S. Geological Survey (USGS) at the Colorado School of Mines (Mines), 1000 18th Street, Golden, Colorado 80401, provide a packaged high performance Vertical Flooded Steam to Water Heat Exchangers for Building Heat and Domestic Hot Water delivered to the EMRF construction site. This project is federally funded by the President Joe Biden's Bipartisan Infrastructure Law (BIL). Therefore, the material used for construction is required to be compliant with the Build America, Buy America Act (BABAA). This NIST MEP Supplier Report seeks a BABAA compliant Heat Exchangers that meets or exceeds the basis of design. The basis of design is a Maxi-Therm steam to water heat exchangers described herein (including additional information). The basis of design heat exchangers meets or exceeds the design requirements including the strict technical requirements, maximum size requirements, maximum delivery schedule, and the maximum cost parameters enclosed. See also the requirements stated in the enclosed specifications, drawings, dimension and performance requirements, and other documents including warranty requirements. Packaged heat exchanger systems (pre-piped and wired controls assembled on a painted and fabricated equipment steel framed and ready for field piping connections) and associated components and accessories include, but are not limited to, the following: 1. Vertical U-tube. 2. Liquid and Steam piping to be Schedule 40 carbon steel. 3. Liquid Condensate piping to be Schedule 80 carbon steel. 4. Stabilizing pump and isolation valves and stainless steel check valve. 5. Modulating electric control valve on the condensate outlet, fail safe, pre-wired to the control panel. 6. Thermowells, electric temperature sensor, with thermometers located at the liquid inlet and outlet, and condensate outlet. 7. Pressure transmitter on steam inlet, flow sensor on the liquid inlet, overheat butterfly security valve on the steam side, start-up valve on the steam inlet. 8. NEMA 4 UL approved control panel, pre-programmed to include the following: a. Programmable controller with optimal control sequence. b. Factory wiring to all sensors and valves. c. Color HMI graphic interface with different users' access levels. d. Access via the building automation system to all parameters for remote monitoring and remote control. e. BACnet (IP) communication protocols are available. f. IoT ready with data acquisition and secure remote access capabilities (ISO 27001 and ISECOM STAR certified) with OPC US Embedded Server. Internet connectivity must be provided to the panel via an ethernet cable by the customer for remote troubleshooting and monitoring. g. Continuous display and datalogging of liquid inlet, water outlet, condensate outlet temperatures, steam pressure, liquid flow in GPM, condensate control valve and main steam valve position (via the feedback output of the valves) and heat transfer rate in BTU/hr. h. Preprogrammed and adjustable alarms for liquid outlet high and low temperature, condensate outlet high temperature, high and low liquid flow as well as high steam pressure. Sensor/valve failure alarm is also standard. i. The outside disconnect switch to be able to locally shut the power to the panel before opening the door. j. Integral network switch and 120V power supply receptacle to plug in a laptop for easy tech support. Laptop can be plugged in with the control panel door closed for more safety. k. Return to last known state after a power outage. 9. Flanged steam trap on condensate outlet, strainer with 40-mesh and blowdown valve on condensate outlet.</p>
Notify Requester Immediately	
State item to be used in	Colorado

Section 2: Technical Information

Type of supplier being sought	Manufacturer
Reason	BABA
Describe the manufacturing processes (elaborate to provide as much detail as possible)	Electronic and mechanical assembly.
Provide dimensions / size / tolerances / performance specifications for the item	See information provided.
List required materials needed to make the product, including materials of product components	Various, see information provided.
Are there applicable certification requirements?	Yes
Details	DOMESTIC WATER HEAT EXCHANGER: A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use. B. ASME Compliance: Where ASME-code construction is indicated, fabricate and label heat-exchanger storage tanks to comply with ASME Boiler and Pressure Vessel Code: Section VIII, Division 1. C. Comply with NSF 61, "Drinking Water System Components - Health Effects; Sections 1 through 9" for all components that will be in contact with water BUILDING HEAT EXCHANGER: A. ASMEASME BPVC-VIII-1 - Boiler and Pressure Vessel Code, Section VIII, Division 01 - Rules for Construction of Pressure Vessels. B. ASME Section II – Material Testing. C. ASME Section V – Non-Destructive Testing. D. ASME Section IX – Welding and Brazing Qualifications. E. AHRI Standard 400 – Liquid -to-Liquid Heat Exchangers. F. TEMA Standards – “Standards of the Tubular Exchanger Manufacturers Association”.
Are there applicable regulations?	No
Are there any other standards, requirements, etc.?	Yes
Details	See above. See the enclosed specification requirements including spare parts, warranty, manufacturer qualifications, delivery, storage, and handling.
NAICS 1	332410 Power boiler and heat exchanger manufacturing
NAICS 2	
Additional Technical Comments	See enclosed specification section and Maxi-Therm basis of design information.

Section 4: Business Information

Estimated potential business volume	Limited to one set of equipment.
Estimated target price / unit cost information (if unavailable explain)	Maximum total costs are the following: Building Heat system is \$326,000 (This includes the product, shipping, start-up, assistance for controls contractor and warranty service.) Domestic Water system is \$125,000 (This includes product, shipping, controls, start-up, and warranty service.). Costs include shipping, start up services including commissioning and coordinating the heat exchangers with Building Automation System, and required minimum manufacturer's warranty (see specifications). Costs also include providing approved submittal paperwork required in the specifications.

When is it needed by?	Maxi-Therm lead time is 20 weeks but no later than 2:00 pm local time the on-site at the following dates. Domestic water heat exchanger needed on site 6/17/2025. Building heat exchanger needed on site 5/29/2025. If the schedule has delivery prior to the dates above, the cost of holding equipment until the project can receive the equipment will not be allowed. Provide written manufacturer's submittal at least 90 days before required by manufacturer for review and approval.
Describe packaging requirements	Crate and package equipment and components for secure and undamaged transportation and delivery.
Where will this item be shipped?	Shipping will be to Golden, Colorado 80401, at the construction site address listed above.

Additional Comments

Is there other information you would like to include?	
---	--

**SECTION 223500
DOMESTIC WATER HEAT EXCHANGERS**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following heat exchangers:
 - 1. Domestic-water-in-coil, steam-to-liquid vertical flooded instantaneous heat exchangers.

1.3 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data with dimensions, locations, and size of tap and performance data, include heat transfer surface area, fouling factors, fluid media and concentrations, materials of construction. Where more than one set of performance parameters are included in the schedule(s) the submittal shall include all multi-variable operating performance data. Include service clearances required for heat exchangers.
- C. Shop Drawings:
 - 1. Design Data: Indicate in sufficient detail to verify that heat exchangers meet or exceed specified requirements.
 - 2. Test Reports: Indicate tube bundle pressure tests.
- D. Certificates: Certify that products meet or exceed specified requirements. Include certification and stamp documentation as required for compliance with respective pressure vessel codes.
- E. Manufacturer's Installation Instructions: Submit manufacturer's published installation requirements.
- F. Operation and Maintenance Data: Include start up and shut down instructions, assembly drawings, and spare parts lists.
- G. Warranty: Submit manufacturer's warranty and ensure forms have been completed in Owner's name and registered with manufacturer.

1.4 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacture, assembly, and field performance of heat exchangers with minimum ten years of documented experience.

- B. Product Options: Drawings indicate size, profiles, and dimensional requirements of heat exchangers and are based on the specific system indicated. Refer to Division 01 Section "Product Requirements."
- C. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- D. ASME Compliance: Where ASME-code construction is indicated, fabricate and label heat-exchanger storage tanks to comply with ASME Boiler and Pressure Vessel Code: Section VIII, Division 1.
- E. Comply with NSF 61, "Drinking Water System Components - Health Effects; Sections 1 through 9" for all components that will be in contact with water.

1.5 COORDINATION

- A. Coordinate size and location of concrete bases with Architectural and Structural Drawings.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Provide temporary end caps on all openings, to protect the internals from entry of foreign material.

1.7 WARRANTY

- A. See Section 01 78 00 - Closeout Submittals, for warranty requirements. In addition to these requirements, the manufacturer(s) shall provide the following additional extended warranty for the product described:
 - 1. Provide five-year manufacturers limited warranty for steam to liquid vertical flooded type heat exchanger condensate control valve and heat exchanger components.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, provide the product indicated on Drawings or a comparable product by one of the following:
 - 1. Maxi-Therm, (No Substitutions)

2.2 DOMESTIC, STEAM-TO-LIQUID VERTICAL FLOODED HEAT EXCHANGERS

- A. General: Provide the type, sizes, capacities, and performance as scheduled on the drawings.
- B. Provide steam-to-water packaged heat exchanger factory pre-piped and wired controls assembled on a fabricated equipment skid, ready for field piping connections.
- C. The factory-built heat exchanger system shall include the following components and functions:
 - 1. Heat Exchanger: Vertical U-tube
 - 2. Liquid & Steam Piping: Schedule 80 carbon steel

3. Stabilizing pump with, isolation valves and stainless steel check valve.
4. Thermowells, modulating electric control valve on the condensate outlet, electric temperature sensor, with thermometers located at the liquid inlet and outlet, and condensate outlet.
5. Pressure transmitter on steam inlet, flow sensor on the liquid inlet, over heat butterfly security valve on the steam side, start-up valve on the steam inlet,
6. NEMA 4 UL approved control panel, pre-programmed to include the following:
 - 1) Programmable controller with optimal control sequence.
 - 2) Factory wiring to all sensors and valves.
 - 3) Color HMI graphic interface with different users' access levels.
 - 4) Access via the building automation system to all parameters for remote monitoring and remote control.
 - 5) BACnet (IP) communication protocols are available.
 - 6) IoT ready with data acquisition and secure remote access capabilities (ISO 27001 and ISECOM STAR certified) with OPC US Embedded Server. Internet connectivity must be provided to the panel via an ethernet cable by the customer for remote troubleshooting and monitoring.
 - 7) Continuous display and datalogging of liquid inlet, water outlet, condensate outlet temperatures, steam pressure, liquid flow in GPM, condensate control valve and main steam valve position (via the feedback output of the valves) and heat transfer rate in BTU/hr.
 - 8) Preprogrammed and adjustable alarms for liquid outlet high and low temperature, condensate outlet high temperature, high and low liquid flow as well as high steam pressure. Sensor/valve failure alarm is also standard.
 - 9) The outside disconnect switch to be able to locally shut the power to the panel before opening the door.
 - 10) Integral network switch and 120V power supply receptacle to plug in a laptop for easy tech support. Laptop can be plugged in with the control panel door closed for more safety.
 - 11) Return to last known state after a power outage.
7. Flanged steam trap on condensate outlet, strainer with 40-mesh and blowdown valve on condensate outlet.
- D. Tubes: Vertical U-tube type with 3/4 IN. OD minimum vented, double-wall cupro-nickel (90/10 CuNi) tubes suitable for 150 PSIG working pressure and 375 °F.
- E. Shell: Steel pipe with threaded or flanged piping connections and necessary pipe tap connections, steel saddle and attaching U-bolts, prime coated.
- F. Heads: Cast iron or fabricated steel with 304 stainless steel tube sheets; flanged for piping connections.
- G. Water Chamber and Tube Bundle: Removable for inspection and cleaning.
- H. Design: Heating fluid in shell and heated fluid in tubes.
- I. Certification: ASME Certified construction.

- J. Accessories:
 - 1. Two (2) steam traps as drip traps.
 - 2. Stainless steel vacuum breaker for steam inlet piping.
 - 3. Stainless steel air vent for the steam inlet piping.
 - 4. Condensate mixer with integrated check valves.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Complete installation of heat exchanger(s) in compliance with the piping details shown on the drawings and otherwise as indicated in the contract documents.
- C. Connect all inlet/outlet piping connections with unions or flanges, and shut-off valves.
- D. Install pipe support or hangers as required, to prevent the weight of the pipe free from imposing stress on the equipment flanges as recommended by the heat exchanger manufacturer.
- E. For all heat exchangers, arrange and install piping, valves, controls, gauges, piping specialties, accessories, etc. to allow for easy disassembly of piping connections, with minimal disturbance to equipment and adjacent piping, in order to provide maintenance and service access. This includes tube removal for shell and tube heat exchangers, drawback space for plate and frame exchangers to allow separating of plates for cleaning or replacement; and replacement or removal of brazed plate type heat exchangers.
- F. Install heat exchangers on concrete housekeeping pad. Refer to Section 22 05 29.
- G. For shell and tube heat exchangers, provide shop fabricated elevated supports stands constructed of ASTM A36 carbon steel to accommodate support cradle supplied by the heat exchanger. Refer to Section 22 05 29 for support stand requirements. Pitch shell to drain condensate completely.
- H. Install all temperature, pressure, flow switches, flow meters, wells, taps, etc., and all other pipe connections as required for the Temperature Control Contractor to complete their work.
- I. For domestic water side(s) of heat exchangers refer to the following sections for additional requirements:
 - 1. Section 22 05 19 Meters & Gauges
 - 2. Section 22 11 16 Domestic Water Piping
 - 3. Section 23 11 19 Domestic Water Piping Specialties
- J. For steam side(s) of heat exchangers refer to the following sections for additional requirements:
 - 1. Section 23 05 19 Meters & Gauges
 - 2. Section 23 22 13 Steam & Condensate Piping
 - 3. Section 23 22 33 Steam Specialties

- K. Pipe water relief valves to nearest floor drain, which will not result as a trip hazard.
 - L. Pipe steam safety relief valves to outside the building and terminate in manner to avoid dangerous discharge to humans. Provide drip pan elbow at relief valve as recommended by the relief valve manufacturer.
 - M. Pipe drain valves to nearest floor drain, which will not result as a trip hazard.
 - N. Unless specifically noted otherwise all heat exchangers shall be insulated in accordance with Section 22 07 00 Plumbing Insulation.
 - O. Where applicable, field install all electrical devices provided by the heat exchanger manufacturer not specified to be factory-installed.
 - P. Where indicated on drawings, provide heat exchanger with 1-1/4" hot water stabilization piping branch. Minimum developed length, 30'-0". Refer to manufacturer's installation data for additional information.
- 3.2 STEAM TO WATER HEAT EXCHANGER TRIM
- A. Refer to piping detail on the drawings.
 - B. Shell: Pressure gauge tapping with pigtail siphon, vacuum breaker
 - C. Steam Piping: Provide piping as indicated, including control valve with 3-valve bypass, strainer, and pressure gage on inlet; condensate dirt leg, steam trap with 3-valve bypass, strainer, and check valve on outlet; air vent or vacuum breaker on shell.
 - D. Water Inlet: Thermometer well, pressure gauge tapping, valved drain.
 - E. Water Outlet: Thermometer well for temperature regulator sensor, ASME rated pressure and temperature relief valve, thermometer well, pressure gauge taps.
- 3.3 FIELD QUALITY CONTROL
- A. See Section 01 4000 - Quality Requirements, for additional requirements.
 - B. Provide manufacturer's field representative to test, inspect, instruct, and oversee equipment startup.
 - C. Inspect for and remove blocks, shipping bolts, and tie-down straps.
 - D. System Flushing & Cleaning: Do not allow flow thru heat exchanger until the piping systems are flushed and clean free of oils, grease, slag and other contaminants. Provide temporary by-pass piping near piping connections on system side of shut-off valves, to circulate chemical treatment for flushing and cleaning.
 - E. Operational Test: Place each heat exchanger in to service to confirm it is operating properly.
 - F. Controls and Safety Switches: Test, adjust, and replace damaged/malfunctioning controls and equipment.
 - G. Coordinate all temperature control work with the BAS Control Contractor, Section 23 09 93 - Sequence of Operations for HVAC Controls.

- H. Malfunctioning Units: Remove, replace, and retest as specified above.
- 3.4 COMMISSIONING
- A. See Section 01 91 13 - General Commissioning Requirements, for commissioning requirements.
 - B. See Section 23 08 00 – Commissioning of HVAC for additional commissioning requirements.
 - C. Perform functional tests as required by the Manufacturer and the Commissioning Agent’s written commissioning plan.
- 3.5 ADJUSTING AND CLEANING
- A. Cleaning: Clean factory-finished surfaces free of dust and debris using an approved cleaning solution and drying cloth. Repair any marred or scratched surfaces with manufacturer’s touch-up paint. Unit shall be in “like-new” condition upon turn over to Owner.
- 3.6 SPARE PARTS
- A. General: Furnish to Owner, on spare gasket for each flanged connection for each heat exchanger and wrench. Provide the Owner a receipt for spare parts delivered; obtain a signature with date. Include copy of signed receipt with the O & M Manuals.
- 3.7 TRAINING
- A. Training: For heat exchanger type, provide services of manufacturer's technical representative for two (2) hours, to instruct Owner's personnel in operation and maintenance of equipment. Schedule with Owner and provide at least one (1) week notice to Contractor and Engineer of training date.

END OF SECTION

**SECTION 23 57 00
HEAT EXCHANGERS FOR HVAC**

PART 1 - GENERAL

1.1 SECTION INCLUDES

- A. Plate & Frame Cleanable Gasketed type heat exchangers.
- B. Steam-to-liquid vertical flooded type heat exchangers.

1.2 RELATED REQUIREMENTS

- A. Drawings, all other Sections of Division 23 and General Provisions of the Contract, including General and Supplementary Conditions, as well as Division 01 Specification Sections, apply to this Section.
- B. All materials, equipment, fabrication and installation shall meet and comply with all adopted current codes, regulations, standards, etc. as applicable to the product(s) specified in the section, as scheduled on the drawings as well as Division 01 and Division 23 related documents whether called for or not.

1.3 REFERENCE STANDARDS

- A. ASME BPVC-VIII-1 - Boiler and Pressure Vessel Code, Section VIII, Division 01 - Rules for Construction of Pressure Vessels.
- B. ASME Section II - Material Testing.
- C. ASME Section V - Non-Destructive Testing.
- D. ASME Section IX - Welding and Brazing Qualifications.
- E. AHRI Standard 400 - Liquid -to-Liquid Heat Exchangers.
- F. TEMA Standards - "Standards of the Tubular Exchanger Manufacturers Association".

1.4 SUBMITTALS

- A. Product Data: Provide data with dimensions, locations, and size of tap and performance data, include heat transfer surface area, fouling factors, fluid media and concentrations, materials of construction. Where more than one set of performance parameters are included in the schedule(s) the submittal shall include all multi-variable operating performance data. Include service clearances required for heat exchangers.
- B. Shop Drawings:
 - 1. Design Data: Indicate in sufficient detail to verify that heat exchangers meet or exceed specified requirements.
 - 2. Test Reports: Indicate tube bundle pressure tests.

- C. Certificates: Certify that products meet or exceed specified requirements. Include certification and stamp documentation as required for compliance with respective pressure vessel codes.
- D. Manufacturer's Installation Instructions: Submit manufacturer's published installation requirements.
- E. Operation and Maintenance Data: Include start up and shut down instructions, assembly drawings, and spare parts lists.
- F. Warranty: Submit manufacturer's warranty and ensure forms have been completed in Owner's name and registered with manufacturer.
- G. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
 - 1. Refer to Division 01 Section "Operation and Maintenance Data", for additional provisions.
- H. Spare Parts
 - 1. Extra Gaskets: One set of each type and size.
 - 2. Plate Type Heat Exchanger Tools: One set of wrenches for disassembly.
 - 3. Provide the Owner a receipt for spare parts delivered; obtain a signature with date. Include a copy of signed receipt with the O & M Manuals.

1.5 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacture, assembly, and field performance of heat exchangers with minimum ten (10) years of documented experience.
- B. In no case shall any manufacturer provide less heat transfer surface area than scheduled on the drawings, regardless of what the calculation indicates. The fouling factors noted on the drawings shall be used to determine heat transfer area.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Provide temporary end caps on all openings, to protect the internals from entry of foreign material.
- B. Handle heat exchangers carefully to prevent damage, breaking, denting, and scoring. Do not install damaged units or components; replace with new.
- C. Store heat exchangers in clean dry place. Protect from weather, dirt, fumes, water, construction debris, and physical damage.
- D. Comply with manufacturer's rigging and installation instructions for unloading heat exchangers and moving them to final location.

1.7 WARRANTY

- A. Refer to Division 01 Section "Closeout Procedures", for warranty requirements. In addition to these requirements, the manufacturer(s) shall provide the following additional extended warranty for the product described:

1. Provide 36-month manufacturer warranty for AHRI certified plate and frame heat exchangers from date of turn over to Owner.
2. Provide 60-month manufacturer's warranty for steam to liquid vertical flooded type heat exchanger and condensate control valve and an 18-month warranty for heat exchanger components and performance.

PART 2 - PRODUCTS

~~2.1 PLATE AND FRAME GASKETED TYPE HEAT EXCHANGER~~

- ~~A. Manufacturers: The manufacturers listed are subject to compliance of all the requirements within the contract documents; provide the product indicated on Drawings or a comparable product by one of the following:
 - ~~1. Ameridex.~~
 - ~~2. Alfa Laval.~~
 - ~~3. Armstrong.~~~~
- ~~B. General: Provide the type, sizes, capacities, and performance as scheduled on the drawings.~~
- ~~C. Frames: Carbon steel with baked epoxy enamel paint (minimum 3-mil thickness), stainless steel side bolts, and shroud. The frame assembly design shall allow for additional plates as noted in the equipment schedule shown on the drawings. Piping connections shall be provided on the fixed frame, with a movable frame at the opposite end.~~
- ~~D. Plates: Stainless steel Type 304. The plate pack shall be covered with an aluminum shroud in accordance with OSHA.~~
- ~~E. Carrying and Guide Bars: The carrying and guide bar surfaces in contact with the plate pack shall be stainless steel. The bolt lengths shall allow for additional plates as noted in the equipment schedule shown on the drawings. A roller bearing shall be provided on the movable cover for all units with port sizes 3-inch or larger.~~
- ~~F. Gaskets: Provide Nitrile rubber gaskets. Gaskets shall be designed to indicate leakage across the sealing gaskets prior to the intermixing of fluids. Gasket surfaces shall be used for sealing plates, and not for plate alignment.~~
- ~~G. Nozzles: Locate nozzles on fixed end plate. For 4-inch and larger, provide studded port connections to align with ANSI Flange connections. Each studded port shall be lined with a material compatible with the process fluid, to prevent process fluid from coming in contact with the painted cover.~~
- ~~H. Design Rating: 150 PSIG at 200 °F.~~
- ~~I. The heat exchanger shall be designed, constructed, and tested in accordance with Section VIII, Division I of the ASME Pressure Vessel Code, and shall be code stamped. ASME nameplate shall be attached on the face of the fixed cover.~~
- ~~J. The heat exchanger shall be hydrostatically factory tested in accordance with the requirements of the ASME Code Section VIII Div. 1, para. UG-99.~~
- ~~K. Provide the following accessories with the heat exchanger:
 - ~~1. Provide Aluminum OSHA Insulated Shroud Enclosure.~~~~

- ~~2. Tie-Rod Protectors.~~
- ~~3. Tie-Rod Nut Wrench.~~

2.2 STEAM TO LIQUID VERTICAL FLOODED TYPE HEAT EXCHANGER

- A. Manufacturers: The manufacturers listed are subject to compliance of all the requirements within the contract documents; provide the product indicated on Drawings or a comparable product by one of the following:
 - 1. Maxi-Therm, (No Substitutions)
- B. General: Provide the type, sizes, capacities, and performance as scheduled on the drawings.
- C. Provide steam-to-water packaged heat exchanger factory pre-piped and wired controls assembled on a painted and fabricated equipment steel frame, ready for field piping connections.
- D. The factory-built heat exchanger system shall include the following components and functions:
 - 1. Heat Exchanger: Vertical U-tube
 - 2. Liquid & Steam Piping: Schedule 40 carbon steel.
 - 3. Liquid Condensate Piping: Schedule 80 carbon steel.
 - 4. Stabilizing pump with isolation valves and stainless-steel check valve.
 - 5. Modulating electric control valve on the condensate outlet, fail safe, pre-wired to the control panel. The valve body shall be of A 216 Gr. WCB cast steel fabrication with ANSI 300 PSIG flanged connections. Control valve shall be provided with digital positioner with position feedback analog output. Actuator to have a manual override.
 - 6. Thermowells, electric temperature sensor, with thermometers located at the liquid inlet and outlet, and condensate outlet.
 - 7. Pressure transmitter on steam inlet, flow sensor on the liquid inlet, overheat butterfly security valve on the steam side, start-up valve on the steam inlet,
 - 8. NEMA 4 UL approved control panel, pre-programmed to include the following:
 - a. Programmable controller with optimal control sequence.
 - b. Factory wiring to all sensors and valves.
 - c. Color HMI graphic interface with different users' access levels.
 - d. Access via the building automation system to all parameters for remote monitoring and remote control.
 - e. BACnet (IP) communication protocols are available.
 - f. IoT ready with data acquisition and secure remote access capabilities (ISO 27001 and ISECOM STAR certified) with OPC US Embedded Server. Internet connectivity must be provided to the panel via an ethernet cable by the customer for remote troubleshooting and monitoring.
 - g. Continuous display and datalogging of liquid inlet, water outlet, condensate outlet temperatures, steam pressure, liquid flow in GPM, condensate control valve and main steam valve position (via the feedback output of the valves) and heat transfer rate in BTU/hr.

- h. Preprogrammed and adjustable alarms for liquid outlet high and low temperature, condensate outlet high temperature, high and low liquid flow as well as high steam pressure. Sensor/valve failure alarm is also standard.
 - i. The outside disconnect switch to be able to locally shut the power to the panel before opening the door.
 - j. Integral network switch and 120V power supply receptacle to plug in a laptop for easy tech support. Laptop can be plugged in with the control panel door closed for more safety.
 - k. Return to last known state after a power outage.
9. Flanged steam trap on condensate outlet, strainer with 40-mesh and blowdown valve on condensate outlet.
- E. Tubes: Vertical u-tube type with 3/4 IN. OD minimum cupronickel (90/10 CuNi) tubes suitable for 150 PSIG working pressure and 375 °F.
- F. Shell: Steel pipe with threaded or flanged piping connections and necessary pipe tap connections, steel saddle and attaching U-bolts, prime coated.
- G. Heads: Cast iron or fabricated steel with 304 stainless steel tube sheets; flanged for piping connections.
- H. Water Chamber and Tube Bundle: Removable for inspection and cleaning.
- I. Certification: ASME Certified construction.
- J. Accessories:
- 1. Two (2) steam traps as drip traps.
 - 2. Stainless steel vacuum breaker for steam inlet piping.
 - 3. Stainless steel air vent for the steam inlet piping.
 - 4. Condensate mixer with integrated check valves.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Complete installation of heat exchanger(s) in compliance with the piping details shown on the drawings and otherwise as indicated in the contract documents.
- C. Connect all inlet/outlet piping connections with unions or flanges and shut-off valves.
- D. Install pipe support or hangers as required, to prevent the weight of the pipe free from imposing stress on the equipment flanges as recommended by the heat exchanger manufacturer.
- E. For all heat exchangers, arrange and install piping, valves, controls, gauges, piping specialties, accessories, etc. to allow for easy disassembly of piping connections, with minimal disturbance to equipment and adjacent piping, in order to provide maintenance and service access. This includes tube removal for shell and tube heat exchangers, drawback space for plate and frame exchangers to allow separating of plates for cleaning or replacement; and replacement or removal of plate type heat exchangers.

- F. Install heat exchangers on concrete housekeeping pad. Refer to Division 23 Section "Common Work Results for HVAC".
- G. Install all temperature, pressure, flow switches, flow meters, wells, taps, etc., and all other pipe connections as required for the Temperature Control Contractor to complete their work.
- H. For liquid side(s) of heat exchangers refer to the following sections for additional requirements:
 - 1. Division 23 Section "Meters & Gauges for HVAC Piping."
 - 2. Division 23 Section "Hydronic Piping."
 - 3. Division 23 Section "Hydronic Specialties."
- I. For steam side(s) of heat exchangers refer to the following sections for additional requirements:
 - 1. Division 23 Section "Meters & Gauges for HVAC Piping"
 - 2. Division 23 Section "Steam & Condensate Piping, Valves, & Specialties."
- J. Pipe water relief valves to nearest floor drain, which will not result as a trip hazard.
- K. Pipe steam safety relief valves to outside the building and terminate in manner to avoid dangerous discharge to humans. Provide drip pan elbow at relief valve as recommended by the relief valve manufacturer.
- L. Pipe drain valves to nearest floor drain, which will not result as a trip hazard.
- M. Unless specifically noted otherwise all heat exchangers shall be insulated in accordance with Division 23 Section "Mechanical Insulation."
- N. Where applicable, field install all electrical devices provided by the heat exchanger manufacturer not specified to be factory-installed.

3.2 STEAM TO WATER HEAT EXCHANGER TRIM

- A. Refer to piping detail on the drawings.
- B. Shell: Pressure gauge tapping with pigtail siphon, vacuum breaker
- C. Steam Piping: Provide piping as indicated, including control valve with 3-valve bypass, strainer, and pressure gage on inlet; condensate dirt leg, steam trap with 3-valve bypass, strainer, and check valve on outlet; air vent or vacuum breaker on shell.
- D. Water Inlet: Thermometer well, pressure gauge tapping, valved drain.
- E. Water Outlet: Thermometer well for temperature regulator sensor, ASME rated pressure and temperature relief valve, thermometer well, pressure gauge taps.

3.3 WATER TO WATER HEAT EXCHANGER TRIM

- A. Refer to piping detail on the drawings.
- B. Water Inlets and Outlets: Thermometer wells, pressure gauge pipe taps.
- C. Heated Water Outlet: Thermometer well for temperature regulator sensor, ASME rated pressure and temperature relief valve, valved drain.

3.4 FIELD QUALITY CONTROL

- A. Provide manufacturer's field representative to test, inspect, instruct, and oversee equipment startup.
- B. Inspect for and remove blocks, shipping bolts, and tie-down straps.
- C. System Flushing & Cleaning: Do not allow flow thru heat exchanger until the piping systems are flushed and clean free of oils, grease, slag and other contaminants. Provide temporary by-pass piping near piping connections on system side of shut-off valves, to circulate chemical treatment for flushing and cleaning.
- D. Operational Test: Place each heat exchanger in to service to confirm it is operating properly.
- E. Controls and Safety Switches: Test, adjust, and replace damaged/malfunctioning controls and equipment.
- F. Coordinate all temperature control work with the BAS Control Contractor, Refer to Division 23 Section "Sequence of Operations for HVAC Controls."
- G. Malfunctioning Units: Remove, replace, and retest as specified above.

3.5 COMMISSIONING

- A. Refer to Division 01 Section "General Commissioning Requirements", for commissioning requirements.
- B. Refer to Division 23 Section "Commissioning of HVAC" for additional commissioning requirements.
- C. Perform functional tests as required by the Manufacturer and the Commissioning Agent's written commissioning plan.

3.6 ADJUSTING AND CLEANING

- A. Cleaning: Clean factory-finished surfaces free of dust and debris using an approved cleaning solution and drying cloth. Repair any marred or scratched surfaces with manufacturer's touch-up paint. Unit shall be in "like-new" condition upon turn over to Owner.

3.7 TRAINING

- A. Training: For heat exchanger type, provide services of manufacturer's technical representative for two (2) hours, to instruct Owner's personnel in operation and maintenance of equipment. Schedule with Owner and provide at least one (1) week notice to Contractor and Engineer of training date.

END OF SECTION

EMRF Maxi-Therm Space Heating and Domestic Water Heating NIST MEP Submittal

Products: Maxi-Therm MCU 1240G-30F-50P and Maxi-Therm MCDW-50G-100F-50P.

Dimensions: Vertical Flooded Heat Exchanger (MCU-1240G-30F-50P) 79"L x 62"W x 122"H. Domestic Hot Water (MCDW-50G-100F-50P) 57"L x 37"W x 85"H.

VERTICAL FLOODED HEAT EXCHANGER SCHEDULE


DESIG.	MFR.	MODEL	SERVICE	TUBE SIDE					SHELL SIDE		OPER. WEIGHT (LB)	REMARKS
				EWT °F	LWT °F	GPM	MBH	FPD (FT W.C.)	STEAM INLET (PSIG)	LBS/HR		
HX-001A	MAXI-THERM	MCU-1240G-30F-50P	BUILDING HEATING WATER	150	180	1,240	17,774	6.92	50	17,604	6,000	(1) (2) (3)
HX-001B	MAXI-THERM	MCU-1240G-30F-50P	BUILDING HEATING WATER	150	180	1,240	17,774	6.92	50	17,604	6,000	(1) (2) (3)

- EACH HEAT EXCHANGER IS SIZED FOR 100% OF THE BUILDING'S LOAD ALLOWING FOR N+1 REDUNDANCY.
- HEAT EXCHANGER SIZED FOR USE WITH 30% PROPYLENE GLYCOL IN HEATING WATER.
- WATER SIDE FOULING FACTOR = 0.0001 HR SQFT DEG F / BTU. STEAM SIDE FOULING FACTOR = 0.00025 HR SQFT DEG F / BTU.

DOMESTIC HOT WATER GENERATOR (STEAM) SCHEDULE

DESIG.	MFR.	MODEL	TUBE SIDE					SHELL SIDE		THERMAL EFF.	APPROX. OP. WEIGHT (LBS)	REMARKS
			EWT °F	LWT °F	GPM	MBH	MAX. P.D. (PSI)	STEAM PRESSURE (PSIG)	LBS/ HR			
DWHX-001	MAXITHERM	MCDW-50G-100F-50P	40	140	50	2,333	5	50	2,500	0.98	2,000	(1) (2)

- REFER TO MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION.
- PRE-PIPED DOUBLE-WALL HEAT EXCHANGER WITH INTEGRATED CONTROLS AND BAS CONNECTIONS.



- CIVIL
- JVA
- 1315 Spruce Street
 Boulder, Colorado 80502
 LANDSCAPING
- Confluence
- 3457 Rinostray Ct., Suite 223
 Denver, Colorado 80216
 STRUCTURAL
- Martin/Martin
- 12499 West Colfax Avenue
 Lakewood, Colorado 80215
 MEP
- Shaffer Baucom Engineering & Consulting
- 3900 S. Wadsworth Boulevard, Suite 600
 Lakewood, Colorado 80235
 MECHANICAL
- DATACOM DESIGN GROUP
- 7600 Burnett Road, Suite 250
 Austin, Texas
 Facility Operator
- Colorado School of Mines
- 1801 18th Street
 Golden, Colorado 80401
 OWNER
- U.S. Geological Survey
- Sunrise Valley Drive
 Reston, Virginia 20192
 FACILITY LOCATION
- Energy & Mineral Research Facility
- 1000 18th Street
 Golden, Colorado 80401
 CONTRACTOR
- Adelson & Peterson Construction
- 797 Ventura Street
 Aurora, Colorado 80011



PROJECT

U.S. GEOLOGICAL SURVEY
 Sunrise Valley Drive
 Reston, Virginia 20192

ENERGY & MINERALS RESEARCH FACILITY
 1000 18TH STREET
 GOLDEN, CO 80401

PR-05 - CONFORMED BUILDING PACK - JANUARY 16, 2024



KEYPLAN

ISSUE CHART

2	PR-05 - CONFORMED BUILDING PACK	2024.01.16
1	DP-3 INTERIOR PACKAGE	2023.11.09
00000	ISSUE	DATE
Job Number: Z21904		
Drawn: DP / TMH / TW		
Checked: CJ		
Approved: GS		


TITLE

PLUMBING - HOT WATER SYSTEM SCHEMATIC

SHEET NUMBER

P50-05


SPEC PROJECT #:	220022
DRAWN BY:	DP/TMH/TW
DESIGNED BY:	DH
CHECK BY:	CEJ
APPROVED BY:	GS



1 DOMESTIC HOT WATER SYSTEM PIPING SCHEMATIC
 SCALE: 1/8" = 1'-0"

MCU - Simplex

Building Heat & Process



Features

- One vertical flooded U-tube heat exchanger
- Condensate control valve with subcooling condensate return below 200°F, resulting in a 0% flash return system
- Automatic steam start-up and shut-off valve
- Total install costs will be 20% less than any other method
- NEMA 4 control panel with an advanced programmable controller, graphic HMI display including BACnet, Lon, Modbus compatibility and remote access. **We are Internet of Things (IOT) ready with a OPC-UA embedded server**
- 5% to 8% energy savings and reduced carbon footprint
- Liquid stability set point at 2°F

MCU - Simplex


Technical Diagram

U.S. PATENT #6,857,467 B2

CAN. PATENT #2,416,353



**maxi·
therm™**
beyond steam™




All Maxi-Therm basic designs do not require:

- Steam pressure reducing station and no steam safety valve to roof
- Condensate return pump station
- Flash tank
- Steam vents to roof

MCU – Simplex Feedback

Domestic Hot Water & Process




Features

- One vertical flooded U-tube heat exchanger
- Condensate control valve with subcooling condensate return below 200°F, resulting in a 0% flash return system
- Automatic steam start-up and shut-off valve
- Total install costs will be 20% less than any other method
- NEMA 4 control panel with an advanced programmable controller, graphic HMI display including BACnet, Lon, Modbus compatibility and remote access. **We are Internet of Things (IOT) ready with a OPC-UA embedded server**
- 5% to 8% energy savings and reduced carbon footprint
- Liquid stability set point at 2°F

MCU – Simplex Feedback

Technical Diagram


U.S. PATENT #6,857,467 B2
CAN. PATENT #2,416,353



All Maxi-Therm basic designs do not require:

- Steam pressure reducing station and no steam safety valve to roof
- Condensate return pump station
- Flash tank
- Steam vents to roof

MCU Simplex for Building Heat or Domestic Hot Water



EQUIPMENT	
Condensate Mixer with Integrated Check Valve by Maxi-Therm	I
Strainer 20 Mesh with Blow Down Valve by Contractor	II
Air Vent 1/2" by Maxi-Therm	III
Strainer with Blow Down Valve by Contractor	IV
Drip Traps 3/4" by Maxi-Therm	V
Pressure Safety Relief Valve by Contractor	VI
Pressure Gauge and Snubber by Contractor	VII
Check Valve by Contractor	VIII
Vacuum Breaker by Maxi-Therm	IX

NOTES	
STEAM PIPING: CARBON STEEL SCH40 LIQUID PIPING: CARBON STEEL SCH40	
DO NOT INSULATE UNIT BEFORE START-UP	
DIMENSIONAL CHANGES MAY BE REQUIRED DURING FABRICATION. ANY CHANGES WILL BE CONFIRMED PRIOR TO SHIPMENT	
THE CIRCULATING PUMP MUST MAINTAIN A CONSTANT FLOW OF 15% OF THE TOTAL FLOW AND MUST PUSH THROUGH THE HEAT EXCHANGER	
IF THE STEAM PRESSURE AT THE HEAT EXCHANGER IS GREATER THAN THE LIQUID PRESSURE TO BE HEATED, THE LIQUID PRESSURE MUST BE AT A MINIMUM OF 25 PSIG	
RECOMMENDED CLEARANCE: 36" ALL AROUND	
ITEMS SHOWN IN DOTTED LINES MUST BE SUPPLIED & INSTALLED BY CONTRACTOR	

Performance Data	
Inlet Steam Pressure (PSIG):	50
Steam Mass Flow (lbs/h):	16473
Water Flow Rate (US gpm):	1240
Inlet Water T° (°F):	150
Outlet Water T°(°F):	180
Liquid Pressure Drop (PSI):	3

APPROXIMATED DIMENSIONS (in)							Approx. Weight (lbs)
OAL	OAW	OAH	Liquid In/Out	Stabilizing Line	Steam Inlet	Condensate	
79	62	122	10	2,5	8	2	5900
Model:							
MCU-1240G-30F-50P							

EVALUATION: COST COMPARAISON WITH EXCHANGER ON FULL LOAD

	CONVENTIONAL	MAXI-THERM	
Pressure	15	50	M = Million PSIG
Energy Transferred	17,774,487	17,774,487	Btu/h
Steam Flow	18801	17604	lbs/h
Flash Rate	4.0	0.0	%
Atmospheric Flash Loss	744.6	0.0	lbs/h
Energy to Heat Condensate	2.131	1.725	MBtu/h
Energy to Heat Make Up	0.170	0.000	MBtu/h
Energy to Vaporize	17.141	16.049	MBtu/h
Total:	19.441	17.774	MBtu/h

Difference = Savings	1.67	MBtu/h
	8.6	

Boiler Efficiency	0.80
--------------------------	------

Total Savings	2.08	MBtu/h
	10.3	

Dollar Savings at	
\$10.00 per 1000 lbs of steam	
2,000 hrs / year	\$42,073
3,000 hrs / year	\$63,109


Carbon Footprint Reduction (using natural gas):	
0.05843 ton of CO₂ per Million BTU	
2,000 hrs / year	243.5 tons of CO₂ per year
3,000 hrs / year	365.2 tons of CO₂ per year


How does the Maxi-Therm system save so much?


1. It condenses steam and extracts heat from the condensate.
2. It consumes less steam because it extracts energy from condensate.
3. It creates **NO FLASH STEAM**.
4. The conventional system does create flash steam.
5. The boiler and DA tank have to heat up the water lost by flash steam.




DATA INPUT FORM










MCU Simplex for Building Heat or Domestic Hot Water



EQUIPMENT	
Condensate Mixer with Integrated Check Valve by Maxi-Therm	I
Strainer 20 Mesh with Blow Down Valve by Contractor	II
Air Vent 1/2" by Maxi-Therm	III
Strainer with Blow Down Valve by Contractor	IV
Drip Traps 3/4" by Maxi-Therm	V
Pressure Safety Relief Valve by Contractor	VI
Pressure Gauge and Snubber by Contractor	VII
Check Valve by Contractor	VIII
Vacuum Breaker by Maxi-Therm	IX

NOTES	
STEAM PIPING: CARBON STEEL SCH40 LIQUID PIPING: CARBON STEEL SCH40	
DO NOT INSULATE UNIT BEFORE START-UP	
DIMENSIONAL CHANGES MAY BE REQUIRED DURING FABRICATION. ANY CHANGES WILL BE CONFIRMED PRIOR TO SHIPMENT	
THE CIRCULATING PUMP MUST MAINTAIN A CONSTANT FLOW OF 15% OF THE TOTAL FLOW AND MUST PUSH THROUGH THE HEAT EXCHANGER	
IF THE STEAM PRESSURE AT THE HEAT EXCHANGER IS GREATER THAN THE LIQUID PRESSURE TO BE HEATED, THE LIQUID PRESSURE MUST BE AT A MINIMUM OF 25 PSIG	
RECOMMENDED CLEARANCE: 36" ALL AROUND	
ITEMS SHOWN IN DOTTED LINES MUST BE SUPPLIED & INSTALLED BY CONTRACTOR	

Performance Data	
Inlet Steam Pressure (PSIG):	50
Steam Mass Flow (lbs/h):	2475
Water Flow Rate (US gpm):	50
Inlet Water T° (°F):	40
Outlet Water T°(°F):	140
Liquid Pressure Drop (PSI):	5

APPROXIMATED DIMENSIONS (in)							Approx. Weight (lbs)
OAL	OAW	OAH	Liquid In/Out	Stabilizing Line	Steam Inlet	Condensate	
57	37	85	2	1,25	3	1,25	1800
Model:							
MCDW-50G-100F-50P							

EVALUATION: COST COMPARAISON WITH EXCHANGER ON FULL LOAD

	CONVENTIONAL	MAXI-THERM	
Pressure	15	50	M = Million
Energy Transferred	2 499 000	2 499 000	PSIG
Steam Flow	2643	2475	Btu/h
Flash Rate	4,0	0,0	lbs/h
Atmospheric Flash Loss	104,7	0,0	%
Energy to Heat Condensate	0,300	0,243	lbs/h
Energy to Heat Make Up	0,024	0,000	MBtu/h
Energy to Vaporize	2,410	2,256	MBtu/h
Total:	2,733	2,499	MBtu/h

Difference = Savings	0,23	MBtu/h
	8,6	%

Boiler Efficiency	0,80
--------------------------	------

Total Savings	0,29	MBtu/h
	10,3	%


<i>Dollar Savings at</i>	
<i>\$10,00 per 1000 lbs of steam</i>	
<i>2 000 hrs / year</i>	\$5 915
<i>3 000 hrs / year</i>	\$8 873


<i>Carbon Footprint Reduction (using natural gas):</i>	
<i>0,05843 ton of CO₂ per Million BTU</i>	
<i>2 000 hrs / year</i>	34,2 tons of CO₂ per year
<i>3 000 hrs / year</i>	51,3 tons of CO₂ per year


How does the Maxi-Therm system save so much?


1. It condenses steam and extracts heat from the condensate.
2. It consumes less steam because it extracts energy from condensate.
3. It creates **NO FLASH STEAM**.
4. The conventional system does create flash steam.
5. The boiler and DA tank have to heat up the water lost by flash steam.











An Enlightening Dream 02 | Vision 06 | Our Capacity 08 | Steam Has All The Answers 10 | Atypical Design 14 | Advantages 16 | End Users 24
The Brainstorming Team 26 | Our Partners 30 | World Class Training 32 | How 34




maxi·
therm™
beyond steam™



AN ENLIGHTENING dream

WE BELIEVE
IN A WORLD
THAT CAN
UNITE AND
STRIVE
for an unprecedented
level of self-sustainability.



After spending 30 years working in the industrial and institutional side of steam optimization, I needed a new challenge and a higher purpose. So when my wife Jacqueline suggested in 1998 to start our own business, I didn't hesitate and decided to take a leap of faith. I secured a bank loan and began setting up a world-class research and development laboratory. We put together a team of experts who believed in my ambition and we tested, re-tested and enhanced European methods until we finally came up with a truly unique and innovative concept in 2004.

We reached our first significant milestone when we were granted US and Canadian patent rights in 2004. The following year, my visionary instincts were recognized by ASHRAE, as I received a coveted Technology Award.

In 2005, we founded Maxi-Therm Inc., and today I am proud to say that our dedicated team works with highly qualified staff resources from 21 exclusive US partners to continuously innovate in the steam solutions market.

Jacqueline Labrosse Lach
Jacqueline Labrosse Lach
Co-Founder

Raymond Lach
Raymond Lach
CEO & Founder



rethinking

THE STATUS QUO



vision

The goal at Maxi-Therm was to put together a team of passionate, visionary people dedicated to finding innovative ways of using steam for building heat and domestic hot water. What started as a small business has grown into a large company with exclusive representation in most major US cities. Our people are human, engaged and committed to the vision of contributing to a more sustainable world.

“We are all
Maxi-Therm.”

- Walter Kuzia



OUR CAPACITY

- **5 PATENT DESIGN CONCEPTS**

Maxi-Therm is an innovative package solution manufacturer with four patent design concepts, as well as an international patent pending zero-lag feature.

- **STRUCTURAL & SEISMIC DESIGN FEATURES**

Maxi-Therm package solutions are engineered with structural and seismic design features. Our service capacity includes local certified tech and engineering in New Jersey, Massachusetts and Chicago.

- **BRAINSTORMING TEAM**

Our engineering group employs a brainstorming team consisting of specialized senior professionals who continuously update and modernize our concepts, both mechanically and electronically.

- **15,000 SQ FT**

Maxi-Therm has four manufacturing and engineering facilities totalizing 15,000 sq ft to assist customers in purchasing the highest quality products and services. One of our facilities meets ISO 9001 quality management and quality assurance standards.


STEAM HAS ALL THE

answers



THE ANSWERS

The Ultimate Package using high or low pressure steam, fully redundant zero lag system with only one steam inlet connection, one condensate outlet that can react positively to a back pressure, one liquid inlet and one liquid outlet connection, no steam pressure reducing station, and no steam vents to roof.



Circulating pumps
50 HP

VFD variable
frequency drives

Main disconnect power

Primary control panel with
remote access connected
to building management
system - BMS
IoT ready

2200 US gpm heat
exchangers (2)
20°F rise
85 PSIG steam
pressure

Secondary control panel
with remote access
connected to building
management system - BMS
IoT ready

ATYPICAL design

Any innovative system is only as effective as it is simple to use. That's why we've designed a control panel that makes every step easy to manage. A NEMA 4 and UL certified control panel with an advanced programmable controller that allows the user to set-up all the options. An intuitive, easy-to-use GRAPHIC HMI display including BACnet, LonWorks, and Modbus compatibility. Remote access capability allows advanced and real-time technical support. An Uninterruptible Power Supply (UPS) switches to battery mode to prevent any downtime in the event of an electricity outage.

An intuitive
easy-to-use
HMI display

We are
Internet of Things (IoT)
ready with a OPC-UA
embedded server

Advantages

Since 2002, our ground-breaking technology allows us to flood the steam heat exchanger and stabilize the liquid outlet temperature. We proudly manufacture high-efficiency steam-to-liquid vertical flooded units for building heat and domestic use, transferring both steam's latent and sensible heat in a 0% flash return system, even at very high steam pressure, and taking into account super-heated steam.





20%

LESS ON TOTAL
INSTALLED
COSTS




LESS
MAINTENANCE

No steam pressure
reducing station,
no steam relief valve,
no condensate
pumping station.



40%

SPACE SAVING




A CLOSED
LOOP

No steam vents to roof,
no flash tanks.



5 TO 16%

LESS ENERGY
CONSUMPTION AND
CARBON FOOTPRINT
REDUCTION



STABILITY OF
LIQUID SET POINT
TEMPERATURE

+/- 2°F

Steam is more efficient than people think.

Over the last several years, as customers chose the natural gas line available to install condensing boilers, they have become aware of the short life cycle of some major components, as well as the high maintenance costs to maintain the operation of these condensing boilers.

Maxi-Therm has simplified the steam-to-liquid solution to a point where there is only one moving part, a very small condensate control valve, meaning that steam is in fact far more efficient than people think.

Moreover, since 2012 the US Department of Energy recommends installing a saturated steam turbogenerator to not only control the reduced steam pressure required, but also to generate electrical power.

why?

REASON 1



SAFETY

Have you ever noticed how quickly we fix water leaks from a heating loop compared to a leak in a steam line? If you don't fix your water leak, you will likely end up with a major mess in your mechanical room. If a natural gas leak occurs, the repair will be considered an emergency, no matter the cost. However, the same steam leak can be present for years before it requires special attention.

REASON 2



THE MAXI-THERM ADVANTAGE

By avoiding pressure-reducing stations, condensate pump stations, big control valve stations on the steam side and the need for steam safety valves to the roof, we can cut the typical maintenance budget of a conventional steam system by more than 75%.

REASON 3



FUEL BACK-UP

Dual fuel burners are typically used in case of a natural gas shortage. However, assuming you don't need dual fuel, is it a good idea to rely on natural gas for the next 15 years? If one day it makes more sense to use another fuel by having a central plant, you will be able to change the burner or boiler and keep the same steam network system for building heat, domestic hot water and steam to steam.

REASON 4



DISTRICT CENTRAL STEAM HEATING SYSTEM

If you're considering buying steam energy for building heat from a district central steam heating plant or other source, you should take a look at our systems that integrate a steam turbogenerator or a steam motor to generate electrical power and add a steam absorption chiller to produce more electrical power in the summer.



end users

THEY'VE PUT THEIR
TRUST IN MAXI-THERM



UNIVERSITIES

VANDERBILT UNIVERSITY | DUKE UNIVERSITY | EASTERN WASHINGTON STATE UNIVERSITY
UNIVERSITY OF NORTH CAROLINA | MONTCLAIR STATE UNIVERSITY | UNIVERSITY OF CHICAGO
HARVARD UNIVERSITY | PENN STATE UNIVERSITY | YALE UNIVERSITY | UNIVERSITY OF PENNSYLVANIA
WEST WASHINGTON STATE UNIVERSITY | COLORADO SCHOOL OF MINES | UNIVERSITY OF NEW
MEXICO | UNIVERSITY OF VERMONT | GRAND VALLEY STATE UNIVERSITY | CENTRAL MICHIGAN
STATE UNIVERSITY | TOWSON UNIVERSITY | UNIVERSITY OF COLORADO | UNIVERSITY OF
WISCONSIN MADISON | OHIO STATE UNIVERSITY | LOYOLA UNIVERSITY CHICAGO



HOSPITALS

WISTAR CANCER CENTER | ST-VINCENT | WAUKESHA | PROVIDENCE ALASKA | PENN MEDICINE
CHILDREN'S HOSPITAL OF PHILADELPHIA | MARTHA JEFFERSON | LUTHERAN GENERAL
KING'S DAUGHTER | JOHN HOPKINS | JERSEY SHORE MEDICAL | BOSTON CHILDREN'S HOSPITAL
ELKHART GENERAL | BALL MEMORIAL | ADVOCATE GOOD SHEPHERD | RUSH COPLEY



PROCESS

COCA-COLA | MILLERCOORS | ARTISAN MEAT | BAE LOGISTICS | COOPER'S HAWK VINEYARDS



PHARMACEUTICAL

MERCK | TELIGENT | WYETH AYERST | B. BRAUN | PFIZER | ALNYLAM



NUCLEAR

ONTARIO POWER GENERATION



THE BRAINSTORMING team

Our engineering group employs a brainstorming team consisting of specialized senior professionals who continuously update and modernize our concepts, both mechanically and electronically.

Our regular two-day brainstorming sessions take place in inspiring locations, far away from the office, which allows us to come up with fresh ideas about our common passion: steam.

**“I AM SURROUNDED
BY WONDERFUL PEOPLE”**

– Raymond Lach


RAYMOND LACH

CEO & founder

Raymond Lach started in the steam business in 1970 and worked for 24 years as a rep for Armstrong Machine Works in Michigan. With the help of his wife Jacqueline, he then founded a company with a team of experts to meet specified industry requirements in steam-to-liquid package solutions.

From 1998 to 2004, Raymond explored the European method of flooded design, enhanced its concept and was granted US and Canadian patent rights in 2004.

In 2005, Raymond founded Maxi-Therm and today works with a highly qualified staff of exclusive US partners to continuously innovate in the steam solutions market.





**PATRICK
LACH**

Vice President Sales & Business Development.

Maxi-Therm



**GABRIEL
COSSETTE**

Vice President Operations & Engineering.

Maxi-Therm



**WALTER
KUZIA**

U.S. Shareholder & Exclusive MTI Distributor, Connecticut and Massachusetts.

Little Inc



**JEFF
BAILEY**

U.S. Shareholder & Exclusive MTI Distributor, Applied Thermal Solution Inc, New Jersey and Philadelphia.

Maxi-Therm Service Department



**CHRIS
LITTLE**

Co-owner Little Inc & Exclusive MTI Distributor, Boston, MA.

Director of Maxi-Therm Service Department in the US



**TONY
RANALLO**

Co-owner BoilerSource & Exclusive MTI Distributor, Chicago, IL.

Maxi-Therm Service Department

BRAINSTORMING
team

professionals



**ROBERT
KNOX**

Regional Sales Manager, Colorado.


Maxi-Therm



**MARIE-
HÉLÈNE
BOUCHARD**

Software & Controls Engineer.

Maxi-Therm



**MAXIME
MÉNARD**

Software & Controls Engineer.

Maxi-Therm

we are



here

World class

TRAINING

Headquartered in Montreal, Canada, Maxi-Therm is the proud owner of a leading-edge laboratory that is unique in the industry. Equipped with a 1,000,000 BTU/h capacity 100 psig steam boiler, this is where we test and demonstrate the performance and stability of temperature setpoint of our latest innovations.

We also invite our customers to a 1½ day technical seminar on steam applications, including our innovative products like the vertical flooded concept and the steam-to-steam generator for humidification or sterilization, and to learn about our steam turbogenerator that generates electrical power.




“Thanks so much for inviting me up to the Maxi-Therm seminar! The learning content, the hand-out materials and the hands-on lab were all outstanding. I felt at ease in the more intimate setting to learn and ask questions. I appreciated your open and honest approach to what the products are about, the inventive spirit that constantly seeks to improve or customize products to perfectly fit an application, and personal investment and sacrifice that stand behind the Maxi-Therm products.”

- Testimonial from attendee

“I would like to thank everyone at Maxi-Therm for the opportunity to attend your Montreal seminar. I found the information covered by you and your team in the subject of steam management extremely educational and insightful. The expertise and professionalism conducted during the class is among the very best, and dialog between colleagues was extremely informative. In my opinion, systems created at Maxi-Therm are innovative and cutting edge. As for the hospitality, it is world class and has left me knowing that the people at Maxi-Therm are not only at the top of their profession, but they are also the top among hosts. Thank you once again.”

- Testimonial from attendee






how?



ASHRAE
Technology
Award, June 2005.
Flooded Steam-
to-Water Vertical
Heat Exchanger



At Maxi-Therm, we're committed to innovation in heat transfer, and the coveted ASHRAE Technology Award we've received shows it's paying off.

Our innovative, efficient steam-to-water heat exchanger technology optimizes the net output energy produced by steam, as opposed to conventional shell-and-tube heat exchangers. By modulating the condensate, the flooded vertical heat exchanger varies the exchange surface. The energy input of the flooded vertical heat exchanger is 85% of the conventional horizontal heat exchanger for the same net energy produced. The exchanger has a stable temperature set-point by modulating the condensate, not the steam.

To us, the ASHRAE award is an inspiration to continue innovating, to continue searching for low-cost, energy-efficient solutions that leave the smallest possible footprint.

* The backpressure turbogenerator is an option recommended by the U.S. Department of Energy.



imagine

A SOLUTION

more energy-efficient than ever, integrating a control panel with remote access connected to building management system - BMS - IoT ready, at a low installation cost, and one that leaves the smallest possible footprint.

Others have imagined what it might be like.
We've made it happen.

Welcome to  maxi·therm™

We are IoT ready

