MEPNN Supplier Scouting Opportunity Synopsis

Section 1: General Information		
Scouting Number	2025-347	
Item to be Scouted	BABA Compliant Flooring	
Days to be scouted	30	
Response Due By	10/10/2025	
Description	BABA Compliant: Linoleum Sheet Flooring: Homogeneous wear layer bonded to backing, with	
Section 2: Technical Inform		
Type of supplier being sought	type specified.	
Details	BABACKIOSINUITE TO CERtified manufacturers	
Reason	3. Thickness: 0.100 inch, minimum, excluding backing.	
Describe the manufacturing processes (elaborate to provide as much detail as possible)	Bondtsip conjugation and the BABAA compliant manufactured products ନ୍ୟୁ ହେଉଁ ଓ ଓ ଓ ଓ ଅନ୍ୟୁ ଓ ଓ ଅନ୍ୟୁ ଓ ଓ ଅନ୍ୟୁ ଅନ୍ୟ	
Provide dimensions / size / tolerances / performance specifications for the item	Seletate the specs and mechanical schedule for more information.	
List required materials needed to make the product, including materials of product components	See attached specs and mechanical schedule for more information.	
Are there applicable certification requirements?	Yes	
Details	Build America, Buy America Act (BABAA) compliant	
Are there applicable regulations?	Yes	
Details	Must be able to submit BABAA manufactured product self-certification manufactured product letter that details a compliant product.	
Are there any other stndards, requirements, etc.?	No	
Additional Technical Comments	See attached specs and mechanical schedule for more information.	

Section 4: Business Information	
Estimated potential business volume	TBD post selection. Cost should be the best available, and cannot increase the project cost by 25%.
Estimated target price / unit cost information (if unavailable explain)	TBD post selection. Cost should be the best available, and cannot increase the project cost by 25%.
When is it needed by?	Q1 2026
Describe packaging requirements	Must arrive undamaged

Where will this item be shipped?	Colorado
Additional Comments	
Is there other information you would like to include?	Nationwide Search Provide written documentation in response to the Supplier Scouting request of being a current Build America Buy America Act compliant Flooring manufacturer with experience in manufacturing the system components, meeting the product performance requirements. Information on BABAA compliance requirements can be found at the Made in America Office link https://www.madeinamerica.gov/.

BHA COTTONWOOD

1394,1374,1355 Cottonwood Broomfield, CO 80020 Caddis No. 2304 **GMP SET** Feb 4, 2025

SECTION 096500 RESILIENT FLOORING

PART 2 PRODUCTS

1.01 SHEET FLOORING

- A. Linoleum Sheet Flooring: Homogeneous wear layer bonded to backing, with color and pattern through wear layer thickness.
 - 1. Minimum Requirements: Comply with ASTM F2034, Type corresponding to type specified.
 - 2. Backing: Jute fabric.
 - 3. Thickness: 0.100 inch, minimum, excluding backing.
 - 4. Seams: Heat welded.
 - 5. Pattern: Solid color.
 - 6. Color: As indicated on drawings.
 - 7. Color: To be selected by Architect from manufacturer's full range.
- B. Welding Rod: Solid bead in material compatible with flooring, produced by flooring manufacturer for heat welding seams, and in color matching field color.

1.02 TILE FLOORING

- A. Vinyl Tile: Printed film type, with transparent or translucent wear layer; acoustic interlayer or backing.
 - 1. Minimum Requirements: Comply with ASTM F1700, Class III.
 - 2. Square Tile Size: 20 by 20 inch, nominal.
 - 3. Plank Tile Size: 9 by 59 inch, nominal. Refer Interior Design schedules for Common House and units.
 - 4. Wear Layer Thickness: 0.012 inch in dwelling units, 0.020 inch at Common House.
 - 5. Total Thickness: 0.20 inch.
 - 6. Tile Edge: Straight.
 - 7. Pattern: As indicated on drawings / finish schedule.
 - Color: As indicated on drawings. Refer Interior Design schedules for Common House and units.
 - 9. Color: To be selected by Architect from manufacturer's standard range.
 - 10. Free of phthalate additives.

1.03 RESILIENT BASE

- A. Resilient Base: ASTM F1861, Type TS, rubber, vulcanized thermoset; style as scheduled.
 - 1. Height: 4 inches.
 - 2. Thickness: 0.375 inch.
 - 3. Finish: Satin.
 - Color: As indicated on drawings. Refer Interior Design drawings for Common House

END OF SECTION

Resilient Flooring 096500 - 81 /1