MEPNN Supplier Scouting Opportunity Synopsis

Section 1: General Information			
Scouting Number	2025-348		
Item to be Scouted	BABA Compliant Irrigation Backflow		
Days to be scouted	30		
Response Due By	10/10/2025		
Description	BABA Compliant: BACKFLOW PREVENTERS		
Section 2: Technical Information			
	3 Pressure Loss: 12 psig maximum, through middle 1/3 of flow range		

Type of supplier being sought	3. Pressure Loss: 12 psig maximum, through middle 1/3 of flow range. 4. Configuration: Designed for horizontal, straight through flow.
Details	ቜለ ያ ልማድ እንተነፀዩ ant self-certified manufacturers
Reason	5ABAGESSOFIBRant self-certified manufacturers a. Valves: Ball type with threaded ends on inlet and outlet of NPS 2 and Smaller;
Describe the manufacturing processes (elaborate to provide as much detail as possible)	Putridetic temporal relative metal appears in the united states and larger.
Provide dimensions / size / tolerances / performance specifications for the item	b. Air-Gap Fitting: ASME A112.1.2, matching backflow-preventer connection. See attached specs and mechanical schedule for more information. Colorado
List required materials needed to make the product, including materials of product components	See attached specs and mechanical schedule for more information.
Are there applicable certification requirements?	Yes
Details	Build America, Buy America Act (BABAA) compliant
Are there applicable regulations?	Yes
Details	Must be able to submit BABAA manufactured product self-certification manufactured product letter that details a compliant product.
Are there any other stndards, requirements, etc.?	No
Additional Technical Comments	See attached specs and mechanical schedule for more information.

	_			_
	A .	Business	1 10 4 0 14 100	a t i a .a
Section	4.	RIICINACC	intorm	ation
Jechon	т.	DUSHICSS		auvii

Jection 4. Dusiness information			
Estimated potential business volume	TBD post selection. Cost should be the best available, and cannot increase the project cost by 25%.		
Estimated target price / unit cost information (if unavailable explain)	TBD post selection. Cost should be the best available, and cannot increase the project cost by 25%.		
When is it needed by?	Q1 2026		
Describe packaging requirements	Must arrive undamaged		
Where will this item be shipped?	Colorado		

Additional Comments Is there other information you would like to include? Nationwide Search Provide written documentation in response to the Supplier Scouting request of being a current Build America Buy America Act compliant Irrigation Backflow manufacturer with experience in manufacturing the system components, meeting the product performance requirements. Information on BABAA compliance requirements can be found at the Made in America Office link https://www.madeinamerica.gov/.

1394,1374,1355 Cottonwood Broomfield, CO 80020 Caddis No. 2304

GMP SET Feb 4, 2025

Division 22 - Plumbing

- 1. Comply with NSF 14, "Plastics Piping Components and Related Materials," for plastic domestic water piping components.
- 2. Comply with NSF 61, "Drinking Water System Components Health Effects; Sections 1 through 9."

PART 2 - PRODUCTS

2.1 VACUUM BREAKERS

- A. Hose-Connection Vacuum Breakers:
 - 1. Standard: ASSE 1011.
 - 2. Body: Bronze, nonremovable, with manual drain.
 - 3. Outlet Connection: Garden-hose threaded complying with ASME B1.20.7.
 - 4. Finish: Rough bronze.

2.2 BACKFLOW PREVENTERS

- A. Reduced-Pressure-Principle Backflow Preventers:
 - 1. Standard: ASSE 1013.
 - 2. Operation: Continuous-pressure applications.
 - 3. Pressure Loss: 12 psig maximum, through middle 1/3 of flow range.
 - 4. Configuration: Designed for horizontal, straight through flow.
 - Accessories:
 - a. Valves: Ball type with threaded ends on inlet and outlet of NPS 2 and smaller; outside screw and yoke gate-type with flanged ends on inlet and outlet of NPS 2-1/2 and larger.
 - b. Air-Gap Fitting: ASME A112.1.2, matching backflow-preventer connection.

2.3 WATER PRESSURE-REDUCING VALVES

- A. Water Regulators:
 - 1. Standard: ASSE 1003.
 - 2. Pressure Rating: Initial working pressure of 150 psig.

2.4 BALANCING VALVES

- A. Copper-Alloy Calibrated Balancing Valves:
 - 1. Type: Ball or Y-pattern globe valve with two readout ports and memory setting indicator.
 - 2. Body: Brass or bronze,
 - 3. Size: Same as connected piping, but not larger than NPS 2.
 - 4. Accessories: Meter hoses, fittings, valves, differential pressure meter, and carrying case.
- B. Accessories: Meter hoses, fittings, valves, differential pressure meter, and carrying case.